

WATER BATH 6 & 12 HOLES

APPLICATION

- Double Walled Water Bath generally used for evaporating liquids for boiling the material.
- Double Walled Water Bath is low cost options for heating / boiling ideal tool for Laboratories, Pharmaceutical, Food & Beverage Industries and Institutions.

KEY FEATURES

- Double walled made of heavy gauge stainless steel.
- Provided with concentric rings (Removable) of 75mm hole.
- Concentric rings can be removed to accommodate containers of various sizes.
- Controls temperature within an accuracy of $\pm 1^{\circ}\text{C}$ by microprocessor based digital temperature indicator cum controller
- Heating by immersion heaters.
- Temperature range ambient above $+5^{\circ}\text{C}$ to 99°C .
- Operating Voltage: 220 Volts AC (50 Hz)

TECHNICAL SPECIFICATION

Model No.	PTE-701 WB A	PTE-701WB B
Internal Size (L X W X D)	300 x 250 x 100mm	350 x 400 x 100mm
Capacity	8 Ltr	14 Ltr
No. of Holes	6	12
Holes Dia.	75 mm	75 mm
Heating Load	1.0 KW	2.0 KW

OPTIONAL - ADD ONS

- Available in thermostat model
- Low water Cut off Device
- Single Walled

